

Перв. примен.		Справ. №		КВИК		Ra 3.2 (✓)	
Подп. и дата		Инв. № дубл.		Инв. инв. №		Взам. инв. №	
Инв. № подл.		Подп. и дата		Инв. № дубл.		Взам. инв. №	
Изм.		Лист		№ докум.		Подп.	
Разраб.							
Пров.							
Т. контр.							
Н. контр.							
Утв.							
КВИК		Лит.		Масса		Масштаб	
		0.002		2:1			
Лист 1		Листов 1		SolidWorks		RUSSIA	

1. Неуказанные пред. отк. размеров по H14,h14±IT14/2

2. Сбеги, недорезы и фаски резьбы по ГОСТ 6357-81

Technical drawing of a hexagonal bolt with a cross-section A-A. The front view shows a hexagonal head with a diameter of 2.5 mm and a length of 14 mm with a tolerance of -0.2 mm. The cross-section A-A shows a hexagonal head with a diameter of 6.4 mm and a length of 11 mm with a tolerance of +0.5 mm. The bolt has a thread with a pitch of 0.65 mm and a lead of 0.4 mm. The surface finish is Ra 3.2. The cross-section A-A shows a hexagonal head with a diameter of 6.4 mm and a length of 11 mm with a tolerance of +0.5 mm. The bolt has a thread with a pitch of 0.65 mm and a lead of 0.4 mm. The surface finish is Ra 3.2. The cross-section A-A shows a hexagonal head with a diameter of 6.4 mm and a length of 11 mm with a tolerance of +0.5 mm. The bolt has a thread with a pitch of 0.65 mm and a lead of 0.4 mm. The surface finish is Ra 3.2.